

Denumire produs: Sistem de discutii

Specificatii tehnice:

Consola de control sistem de discutii PROSYS FM/CTL80L

Powersupply: AC110/220V50/60Hz

Iesire: maxim 100W

Capacitate: maxim 60 microfoane

Dimensiuni (LxWxH): 435 x 269 x 74mm (2U)

Greutate: aprox. 4kg

Culoare si material echipament: carcasa din fier alb-argintie

Temperatura de functionare: 0°C - 40°C

Configuratie:

ACpowerfuse: 1.0amp,220 x 1, 1.0amp, 110 x 1

DCpowerfuse: 10amps x 1

Indicator Status: Semnal Audio supraincarcat LED x 3, Iesire Semnal Audio LED x 3

Monitor: 50mm loudspeaker

Input: AUXIN x 1.0dBV, unbalance, MIC IN x 1600Q, -69dB, unbalance

Output: PAOUT x 1.0dBV, unbalance, AUXOUT x 1.0dBV, unbalance, RECOUT x 1, 10kQ, -20dBV, unbalance, Monitor headphone output x 1

Operation mode: Microphone limiter - 1,2,4,6, Free mode(no limitation)

Control: AUXIN volume x 1, MIC IN volume x 1, PAOUT volume x 1, AUXOUT volume x 1, Mic built-in loudspeaker volume x 1, Monitor loudspeaker volume x 1, Treble volume x 1, Bass volume x 1; Port microfon cu 2 terminale pentru 2 grupuri a cate maxim 40 unitati fiecare

Microfon PROSYS FM/II-01, 02P

Difuzor: 8 + 8Ω, 1W

Consum maxim: 1.4W

Microfon - Condenser, Cardioid, Frecventa raspuns: 50Hz 12.5KHz, Sensibilitate: -43dB±3, Impedanta:
Joasa, Lungime: 48cm, Material gooseneck: Negru cromat - platinat, Greutate: 220gCarcasa – Greutate: aprox. 750g, culoare si material: ABS gri inchis, Cable: 8 core, Temperatura
functionare: 0°C - 40°C**Configuratie:**

Flexible gooseneck mic (2 segments)

Canonsocketformicplug-in

RedLEDringatgooseneckhead

Dual loudspeaker

Prioritybutton (inchairmanunit)

Speaking ON/OFF button

Indicator LED pentru functionare microfon

Cabluri conectare: 2m

15pinD-subconnect

Statie amplificare Inter-M A-60Mixer/amplificator; 60W(RMS)@<1%THD; intrari: combinatie Mic 1-3 XLR/1/4', AUX 1-2; 2
benzi EQ; 8,9 kg**Incinte acustice CES AUDIO CLS-3100**Coloana acustica Contractor; 10W RMS; impedanta: 500Ohm, 1kOhm, 2kOhm, 4kOhm&
8kOhm; SPL(1W,1m): 85dB; gama de frecventa (-10dB): 170Hz...20kHz; dimensiuni: 222 x 94
x 95mm; greutate: 1,31 kg; alb